


Domain Name System (DNS)


Session-1: Fundamentals



Ayitey Bulley
AfNOG 2009 Workshop

Computers use IP addresses. Why do we need names?

- Names are easier for people to remember
- Computers may be moved between networks, in which case their IP address will change.



The old solution: HOSTS.TXT


- A centrally-maintained file, distributed to all hosts on the Internet



• <i>SPARKY</i>	<i>128.4.13.9</i>
• <i>UCB-MAILGATE</i>	<i>4.98.133.7</i>
• <i>FTPHOST</i>	<i>200.10.194.33</i>
• ... etc	

- This feature still exists:
 - */etc/hosts (UNIX)*
 - *c:\windows\hosts*


hosts.txt does not scale

- ✗ Huge file (traffic and load)
 - ✗ Name collisions (name uniqueness)
 - ✗ Consistency
 - ✗ Always out of date
 - ✗ Single point of Administration
 - ✗ Did not scale well
- 


The Domain Name System was born

- DNS is a distributed database for holding name to IP address (and other) information
- Distributed:
 - Shares the Administration
 - Shares the Load
- Robustness and improved performance achieved through
 - replication
 - and caching
- Employs a client-server architecture
- A critical piece of the Internet's infrastructure

DNS is Hierarchical



DNS Database



Unix Filesystem

Forms a tree structure

DNS is Hierarchical (contd.)

- Globally unique names
- Administered in zones (parts of the tree)
- You can give away ("delegate") control of part of the tree underneath you
- Example:
 - sanog.org on one set of nameservers
 - Conference.sanog.org on a different set
 - ws3.conference.sanog.org on another set

Domain Names are (almost) unlimited

- Max 255 characters total length
- Max 63 characters in each part
 - RFC 1034, RFC 1035
- If a domain name is being used as a host name, you should abide by some restrictions
 - RFC 952 (old!)
 - a-z 0-9 and minus (-) only
 - No underscores (_)

Using the DNS

- A Domain Name (like www.sanog.org) is the KEY to look up information
- The result is one or more RESOURCE RECORDS (RRs)
- There are different RRs for different types of information
- You can ask for the specific type you want, or ask for "any" RRs associated with the domain name

Commonly seen Resource Records (RRs)

- A (address): map hostname to IPv4 address
- AAAA (quad A): map a hostname to IPv6 address
- PTR (pointer): map IP address to hostname
- MX (mail exchanger): where to deliver mail for *user@domain*
- CNAME (canonical name): map alternative hostname to real hostname
- TXT (text): any descriptive text
- NS (name server), SOA (start of authority): used for delegation and management of the DNS itself

A Simple Example

- Query: *www.sanog.org.*
- Query type: *A*
- Result:

www.sanog.org. 3600 IN A 204.152.106.61

- **In this case a single RR is found, but in general, multiple RRs may be returned.**
 - (IN is the "class" for INTERNET use of the DNS)

Possible results from a Query

- POSITIVE
 - one or more RRs found
- NEGATIVE
 - definitely no RRs match the query
- SERVER FAIL
 - cannot find the answer
- REFUSED
 - not allowed to query the server

How do you use an IP address as the key for a DNS query

- Convert the IP address to dotted-quad
- Reverse the four parts
- Add ".in-addr.arpa." to the end; special domain reserved for this purpose

e.g. to find name for 193.194.185.25

Domain name: 61.186.152.204.in-addr.arpa.

Query Type: PTR

Result: sanog.isc.org.

Known as a "reverse DNS lookup" (because we are looking up the name for an IP address, rather than the IP address for a name)


Any Questions?



DNS is a Client-Server application

- (Of course - it runs across a network)
- Requests and responses are normally sent in UDP packets, port 53
- Occasionally uses TCP, port 53
 - for very large requests (larger than 512-bytes) e.g. zone transfer from master to slave or an IPv6 AAAA (quad A) record.

There are three roles involved in DNS



Three roles in DNS

- **RESOLVER**
 - Takes request from application, formats it into UDP packet, sends to cache
- **CACHING NAMESERVER**
 - Returns the answer if already known
 - Otherwise searches for an authoritative server which has the information
 - Caches the result for future queries
 - Also known as RECURSIVE nameserver
- **AUTHORITATIVE NAMESERVER**
 - Contains the actual information put into the DNS by the domain owner

Three roles in DNS

- The SAME protocol is used for resolver <-> cache and cache ➡✎✚ auth NS communication
- It is possible to configure a single name server as both caching and authoritative
- But it still performs only one role for each incoming query
- Common but NOT RECOMMENDED to configure in this way (we will see why later).

ROLE 1: THE RESOLVER

- A piece of software which formats a DNS request into a UDP packet, sends it to a cache, and decodes the answer
- Usually a shared library (e.g. libresolv.so under Unix) because so many applications need it
- EVERY host needs a resolver - e.g. every Windows workstation has one

How does the resolver find a caching nameserver?

- It has to be explicitly configured (statically, or via DHCP etc)
- Must be configured with the IP ADDRESS of a cache (why not name?)
- Good idea to configure more than one cache, in case the first one fails

How do you choose which cache(s) to configure?


- Must have PERMISSION to use it
 - e.g. cache at your ISP, or your own
- Prefer a nearby cache
 - Minimises round-trip time and packet loss
 - Can reduce traffic on your external link, since often the cache can answer without contacting other servers
- Prefer a reliable cache
 - Perhaps your own?

Resolver can be configured with default domain(s)

- If "foo.bar" fails, then retry query as "foo.bar.mydomain.com"
- Can save typing but adds confusion
- May generate extra unnecessary traffic
- Usually best avoided

Example: Unix resolver configuration

/etc/resolv.conf



```
search sse.ws.afnog.org  
nameserver 196.200.219.200  
nameserver 196.200.223.1
```

That's all you need to configure a resolver

Testing DNS

- Just put "www.yahoo.com" in a web browser?
- Why is this not a good test?



Testing DNS with "dig"

- "dig" is a program which just makes DNS queries and displays the results
- Better than "nslookup", "host" because it shows the raw information in full

dig sanog.org.

-- defaults to query type "A"

dig sanog.org. mx

-- specified query type

dig 119.2.100.245 sanog.org. mx

-- send to particular cache (overrides
/etc/resolv.conf)

The trailing dot

`dig www.sanog.org.`

- Prevents any default domain being appended
- Get into the habit of using it always when testing DNS
 - only on domain names, not IP addresses or e-mail addresses

```
[field@term /usr/home/field]$ dig @zoe.dns.gh. downloads.dns.gh. a
```

```
; <<>> DiG 9.3.1 <<>> @zoe.dns.gh. downloads.dns.gh. a
```

```
; (1 server found)
```

```
;; global options: printcmd
```

```
;; Got answer:
```

```
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 34963
```

```
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 2, AUTHORITY: 3, ADDITIONAL: 0
```

```
;; QUESTION SECTION:
```

```
;downloads.dns.gh. IN A
```

```
;; ANSWER SECTION:
```

```
downloads.dns.gh. 3600 IN CNAME zoe.dns.gh.  
zoe.dns.gh. 3600 IN A 147.28.0.23
```

```
;; AUTHORITY SECTION:
```

```
dns.gh. 3600 IN NS zoe.dns.gh.  
dns.gh. 3600 IN NS mantse.gh.com.  
dns.gh. 3600 IN NS snshq902.ghanatel.com.gh.
```

```
;; Query time: 275 msec
```

```
;; SERVER: 147.28.0.23#53(147.28.0.23)
```

```
;; WHEN: Sat May 24 00:17:53 2008
```

```
;; MSG SIZE rcvd: 145
```

Understanding output from dig

- STATUS
 - NOERROR: 0 or more RRs returned
 - NXDOMAIN: non-existent domain
 - SERVFAIL: cache could not locate answer
 - REFUSED: query not available on cache server
- FLAGS
 - AA: Authoritative answer (not from cache)
 - You can ignore the others
 - QR: Query/Response (1 = Response)
 - RD: Recursion Desired
 - RA: Recursion Available
- ANSWER: number of RRs in answer

Understanding output from dig

- Answer section (RRs requested)
 - Each record has a Time To Live (TTL)
 - Says how long the cache will keep it
- Authority section
 - Which nameservers are authoritative for this domain
- Additional section
 - More RRs (typically IP addresses for the authoritative nameservers)
- Total query time
- Check which server gave the response!
 - If you make a typing error, the query may go to a default server

Practical Exercise

- Configure Unix resolver
- Issue DNS queries using 'dig'
- Use tcpdump to show queries being sent to cache

